

MCB

252 O

ARKASIL

Type

Maximum system voltage


PDD-27-15-048

PRODUCT DESCRIPTION

Pre-moulded outdoor joint MCB 252 O is designed to connect two XLPE 127/220 kV high voltage cables. Joint MCB 252 O has direct connection of screen wires.

Joint MCB 252 O contains:

- Silicone pre-molded joint body.
- Special tapes for different purposes
- Protective covering from heat shrinkable tubes and sleeves (optionally other protective covering)
- Splice box for protection of optic fibers connection



BASIC COMPONENTS

INSULATOR

- Silicone pre-molded joint body with conductive elements for electrical field control.

CONNECTOR AND SEALING MATERIALS

- Compression sleeve (copper or aluminum depends on cable conductor).
- Sealing and fixing materials
- Optionally it could be sleeve with screws
- Splice box

MCB 252 O

ARKASIL**Type** **Maximum system voltage****PDD-27-15-048****AREA OF APPLICATIONS**

Type	MCB 252 O
Maximum system voltage, kV	252
Cable conductor cross section, mm ²	400 ÷ 2500
Maximum outer sheath diameter, mm	126
Maximum cable insulation diameter(prepared), mm	115

TECHNICAL DATA

Type	MCB 252 O
Electrical data:	
AC voltage withstand test	318 kV for 30 min
Impulse withstand voltage (10+/10- impulses)	1050 kV
Partial discharge test	< 5 pC at 190 kV
Climatic data:	
Climatic version	- 45°C/ + 50°C
Nominal operating current	Limited by cable specification
Short circuit current	Limited by cable specification
Sheath withstand voltages:	
DC voltage, kV	25 kV for 1 min
Mechanical data:	
Approximate weight, kg	80

ALL TYPE TESTS ACCORDING TO REQUIRMENTS

IEC 62067

MCB

252 O

ARKASIL

Type

Maximum system voltage

PDD-27-15-048

MOUNTING

MCB 252 O must be mounted by trained/certified personnel. Mounting area must be protected from dust and moisture. Temperature of mounting should be from +10 to +40 C.

TYPICAL DRAWING

